- 1. (cancelled)
- 2. (cancelled)
- 3. (currently amended) Apparatus for removing water from compressor inlet air comprising:
  - a compressor;
  - an air inlet duct to the compressor;
  - a drain connecting to the inside of the duct;
- a dam extending into air flow through the duct for directing water flowing on an air inlet duct wall toward the drain; the dam comprising a strip with a perforated conduit associated therewith, and

means for lowering pressure in the drain to a pressure less than air pressure in the duct adjacent to the drain[.],

the dam comprising a strip extending diagonally across air flow through the duct and wherein a drain is near the downstream end of the strip.

- 4. (previously presented) Apparatus for removing water from compressor inlet air comprising:
  - a compressor;
  - an air inlet duct to the compressor;
  - a drain connecting to the inside of the duct;

a dam extending into air flow through the duct for directing water toward the drain, wherein the dam comprises a strip with a perforated tube in the strip; and

means for lowering pressure in the drain to a pressure less than air pressure in the duct adjacent to the drain.

## 5. (cancelled)

6. (previously presented) Apparatus for removing water from compressor inlet air comprising:

a compressor;

an air inlet duct to the compressor;

a drain on a non-horizontal wall portion above the bottom of the air duct connecting to the inside of the duct; and

means for lowering pressure in the drain to a pressure less than air pressure in the duct adjacent to the drain, and further comprising a dam extending into air flow through the duct for directing water toward the drain.

- 7. (currently amended) Apparatus for removing water from compressor inlet air comprising:
  - a compressor;

an air inlet duct to the compressor;

a drain connecting to the inside of the duct, and a dam extending into air flow through the duct for directing water flowing toward the dam, and wherein the dam comprises a strip with a perforated tube conduit in the strip; and

means for lowering pressure in the drain to a pressure less than air pressure in the duct adjacent to the drain.

- 8. (original) Apparatus according to claim 6 wherein the dam comprises a strip extending diagonally across the duct and wherein a drain is near the lower end of the strip.
- 9. (cancelled)
- 10. (previously presented) Apparatus for removing water from compressor inlet air comprising:
  - a compressor;

an air inlet duct to the compressor;

a drain connecting to the inside of the duct,

wherein the drain is located on a compressor inlet cone within the inlet air duct, and

means for lowering pressure in the drain to a pressure less than air pressure in the duct adjacent to the drain.

- 11. (original) Apparatus according to claim 10 wherein the drain comprises a dam around at least a portion of the cone and a perforated tube adjacent to the dam.
- 12. (original) Apparatus according to claim 10 wherein the drain comprises a hollow cone and a perforated or porous surface on the cone.

### 13. (cancelled)

- 14. (previously presented) Apparatus for removing water from compressor inlet air comprising:
  - a compressor;
  - an air inlet duct to the compressor;
  - a drain connecting to the inside of the duct;
- a dam extending into air flow through the duct and a perforated tube in the dam; and

a suction device for air and/or water connected to the drain.

- 15. (previously presented) Apparatus for removing water from compressor inlet air comprising:
  - a compressor;

an air inlet duct to the compressor;

a drain connecting to the inside of the duct, wherein the drain comprises a perforated tube extending across a face of the duct; and

a suction device for air and/or water connected to the drain.

- 16. (previously presented) Apparatus according to claim 15 further comprising a dam diverting water to the perforated tube.
- 17. (previously presented) Apparatus for removing water from compressor inlet air comprising:
  - a compressor;
  - an air inlet duct to the compressor;
- a drain connecting to the inside of the duct, wherein the drain comprises a perforated strut in the duct; and
  - a suction device for air and/or water connected to

the drain.

18. (previously presented) Apparatus for removing water from compressor inlet air comprising:

a compressor;

an air inlet duct to the compressor;

a drain connecting to the inside of the duct, wherein the drain is on a non-horizontal wall portion of the air duct;

a dam extending into air flow through the duct for directing water toward the drain; and a suction device for air and/or water connected to the drain.

- 19. (original) Apparatus according to claim 18 wherein the dam comprises a strip with a perforated tube in the strip.
- 20. (original) Apparatus according to claim 18 wherein the dam comprises a strip extending diagonally across the duct and wherein a drain is near the lower end of the strip.

# 21. (cancelled)

- 22. (previously presented) Apparatus for removing water from compressor inlet air comprising:
  - a compressor;

an air inlet duct to the compressor;

a drain connecting to the inside of the duct on a compressor inlet cone within the duct; and

a suction device for air and/or water connected to the drain.

- 23. (previously presented) Apparatus according to claim 22 wherein the drain comprises a dam around at least a portion of the compressor inlet cone and a perforated tube adjacent to the dam.
- 24. (previously presented) Apparatus according to claim 22 wherein the drain comprises a hollow cone and a perforated or porous surface on the cone.
- 25. (previously presented) Apparatus for removing water from compressor inlet air comprising:
  - a compressor;

an air inlet duct to the compressor;

an inlet cone for the compressor within the air inlet duct;

a drain connecting to the inside of the duct on a

surface of the inlet cone; and

a suction device for air and/or water connected to the drain.

- 26. (currently amended) Apparatus according to to claim 25 wherein the inlet cone is hollow and the drain comprises a porous or perforated surface on the inlet cone.
- 27. (original) Apparatus for removing water from compressor inlet air comprising:

a compressor;

hollow inlet air guide vanes for the compressor, wherein the guide vanes have a perforated or porous surface; and

a suction device for water and/or air connected to the hollow interior of the guide vanes.

- 28. (cancelled)
- 29. (previously presented) Apparatus for removing water from compress inlet air comprising:
  - a compressor;
  - an air inlet duct to the compressor;
  - a hollow inlet cone for the compressor within the

air inlet duct, wherein the inlet cone has a perforated or porous surface; and

a suction device for water and/or air connected to the hollow interior of the inlet cone.

30. (original) Apparatus according to claim 29 wherein only a downstream portion of the inlet cone is porous or perforated.

## 31-34. (cancelled)

35. (previously presented) A method of removing water from a compressor inlet air duct comprising:

sucking water through a perforated tube inside the duct; and

sucking water from the tube with a pressure less than air pressure in the duct adjacent to the tube.

#### 36. (cancelled)

37. (previously presented) A method of removing water from compressor inlet air comprising;

sucking water from a hollow strut upstream from the compressor with a pressure less than air pressure adjacent to the suction inlet.

38. (previously presented) A method of removing water from compressor inlet air comprising:

sucking water from a hollow compressor inlet cone within and inlet air duct upstream from the compressor with a pressure less than air pressure adjacent to the suction inlet.

39. (previously presented) A method of removing water from compressor inlet air comprising:

sucking water from a hollow inlet guide vane upstream from the compressor with a pressure less than air pressure adjacent to the suction inlet.